

Faster

Push-Pull High Flow



HF

250 l/min

We are the global reference
in quick-release hydraulic couplings

Faster Spa
Via Ludovico Ariosto, 7
I-26027 Rivolta d'Adda
CR, Italy
T +39 0363 377211
F +39 0363 377333
info@fastercouplings.com
www.fastercouplings.com

BR_HIGH FLOW_09_2017_EN



Requiring higher flow rate?

Choose **HF**

The only one on the market with a flow rate that reaches up to **250 l/min**

We are the market reference for push-pull couplings. We enlarged our standard product portfolio and we are proud to be the only one to offer the **full range of push-pull couplings** up to 250 l/min.

Series 3

Connection allowed with male under residual pressure



3CFPV



3CFHF



3CKHF

Series 4

Connection allowed with both male and female under residual pressure



4SRPV



4SRHF



4SKHF

Technical specifications

Interchange	ISO 7241-1 part A
Size	1/2"
Valve Style	Poppet
Connection Type	Push-Pull
Materials	Carbon steel and Mates500
Operating Pressure	Up to 25 MPa
Disconnection under pressure	Allowed as breakaway according to ISO 5675
Working temperature HF	-25 °C + 100 °C
Flow Rate 0.2 MPa	70 l/min

STANDARD PUSH-PULL

Max Flow Rate: 200 l/min

HIGH FLOW

Max Flow Rate: 250 l/min

HIGH FLOW COMPACT VERSION

Max Flow Rate: 250 l/min
Reduced dimensions: 15 mm shorter

The High Flow feature is guaranteed only when coupling together a Female and a Male High Flow.