





MF MultiQTC

MultiFaster 3 lines (size 06, 08 and 20)



Applications



Technical Specifications

Burst pressure (MPa)

Dash	Size (mm)	Inch	Working Pressure	Flow Rate (l/min)	Spillage (ml)	Male	Female	Male + Female
06	10	3/8"	46 MPa	32	0.01	140	140	140
08	12.5	1/2"	46 MPa	70	0.01	140	140	140
20	31.5	1-1/4"	46 MPa	350	0.03	140	140	140

Material	Steel
Seals	HNBR & PUR
Working temperatures	-20 °C to 100 °C
Surface treatment	MATE 500 (CrIII) MATE 1000 (ZnNi)

Series Interchange	Multifaster
Valve Type	Flat
Connection	Lever
Disconnection	Lever
Connection Under Pressure	Allowed Residual

MultiQTC

Size					Thread Type			FIXED
dash	mm	inch	Housings	Number of Couplings	Thread Type	Standard	Thread	Part Number
06	10	3/8	3	1	F BSPP	ISO 1179-1	BSPP 3/8" FEMALE	MQ3A-06-08-20-A-FC
08	12.5	1/2		1	F BSPP	ISO 1179-1	BSPP 1/2" FEMALE	
20	31,5	1-1/4		1	F BSPP	ISO 1179-1	BSPP 1-1/4" FEMALE	
08	12.5	1/2	3	1	F BSPP	ISO 1179-1	BSPP 1/2" FEMALE	MQ3A-00-08-20-A-FC
20	31,5	1-1/4		1	F BSPP	ISO 1179-1	BSPP 1-1/4" FEMALE	

Size					Thread Type			MOBILE
dash	mm	inch	Housings	Number of Couplings	Thread Type	Standard	Thread	Part Number
06	10	3/8	3	1	F BSPP	ISO 1179-1	BSPP 3/8" FEMALE	MQ3A-06-08-20-A-MC
08	12.5	1/2		1	F BSPP	ISO 1179-1	BSPP 1/2" FEMALE	
20	31.5	1-1/4		1	F BSPP	ISO 1179-1	BSPP 1-1/4" FEMALE	
08	12.5	1/2	3	1	F BSPP	ISO 1179-1	BSPP 1/2" FEMALE	MQ3A-00-08-20-A-MC
20	31,5	1-1/4		1	F BSPP	ISO 1179-1	BSPP 1-1/4" FEMALE	

Spare Parts & Accessories

Female Half				Male Half					
Plates	Lever	Dust cover	Safety Lock	Plates	Seals male	Screws	Plugs	Guiding pins	Dust cover
KIT MQ3A F L	KIT LMQ3A	TM MQ3A	KIT SP5 7MQ	KIT MQ3A M	SK FHV06	KIT VPH	KIT TPMQ 06		TF MQ3A
					SK FHV08		KIT TPMQ 08		
					SK FHV20				

